# STATE OF CALIFORNIA SIGN LIGHTING

Yes

	12
CALIFORNIA ENERGY COMMISSION	111111111111111111111111111111111111111

CEC-	NRCC-LTS-01-E(Revised 08/15)			CALIFORNIA ENERGY COMMISSION
CEF	RTIFICATE OF COMPLIANCE			NRCC-LTS-01-E
Sig	n Lighting			(Page 1 of 5)
Proje	ct Name:			Date Prepared:
A.	General Information			
Pro	ject Address:			
	ation of Sign	Outdoor Signs	☐ Indoor Signs	
	se of Sign Construction	□ New Signs	☐ Sign Alterations	
	e of Lighting Control	☐ New Lighting Controls	☐ Replaced Lighting Controls	☐ Not Installing Lighting Controls
	s Certificate of Compliance includ Mandatory Measures (Lighting Co			ighting Sources
	vialidatory ivieasures (Lighting Co		ed Lighting Power	lighting Sources
	Mandatory Sign Lighting	g Controls		
NC	OTES:			
1.	The same responsible perso	n may install both the sign	lighting power and the sign li	ghting controls, or a different responsible
	person may install the sign l	ighting controls than the res	sponsible person installing the .	sign lighting power.
2.	The Mandatory Measures (	sign lighting controls) are	required for compliance with	the sign lighting Standards. If the person
	responsible for installing the	e sign lighting power is not a	also responsible for the sign lig	hting controls, then the owner of the sign,
	general contractor, or archi	tect shall be responsible to h	nave the sign lighting controls in	nstalled.
3.	If more than one person h	as responsibility for compl	iance, each responsible perso	n shall prepare and sign a Certificate of
				r which they are responsible; alternatively,
	the person with chief respon	nsibility for construction sho	all prepare and sign the Certific	cate of Compliance Declaration Statement
	for the entire construction.	, ,		
1a	. Statements of Respons	sibility		
	•	•	n Statement on this NRCC-LTS-	01-E shall complete Part 1a. Check Yes or
	for all of the following staten			•
	I have responsibility for inst		ols	
1	Yes, complete parts 1a a	nd 1b of this form	No, complete part 1a of this	form
2	There are no existing sign lig	ghting controls and I will be	installing compliant sign lightir	g controls
	Yes		No	
3	There are no existing sign lig	ghting controls and someon	e else will be responsible to ins	tall compliant sign lighting controls
)	Yes		No	
	There are existing sign lighting	ng controls that do not com	ply with the applicable provision	on of §110.9 and §130.3 and I will be
4	installing compliant sign ligh	iting controls		
	Yes		No	
	There are existing sign lighti	ng controls that do not com	ply with the applicable provision	on of §110.9 and §130.3 and someone
5	else will be responsible to ir	ıstall compliant sign lighting	controls	

### CA

SIGN LIGHTING
CEC-NRCC-LTS-01-E(Revised 08/15)

ALIFORNIA ENERGY COMMISSION	A)
-----------------------------	----

CERTIFICATE OF COMPLIANCE	NRCC-LTS-01-E
Sign Lighting	(Page 2 of 5)
Project Name:	Date Prepared:

switch control.  §130.3(a)2A. All outdoor sign lighting is controlled with a photocontrol in addition to an automatic time-switch control, or an astronomical time-switch control.  EXCEPTION to Section 130.3(a)2A: Outdoor signs in tunnels, and signs in large permanently covered outdoor areas that are intended to be continuously lit, 24 hours per day and 365 days per year.  §130.3(a)2B. All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	NA NA
the sign lighting control requirements, that person shall answer all of the following questions:  If there are construction documents, indicate where on the building plans the mandatory measures (sign lighting control) note block can be located:  1 \$\frac{\\$130.3(a)1.}{\} \] All indoor sign lighting is controlled with an automatic time-switch control or astronomical time-switch control.  \$\frac{\}{\}\$130.3(a)2A.} \] All outdoor sign lighting is controlled with a photocontrol in addition to an automatic time-switch control, or an astronomical time-switch control.  EXCEPTION to Section 130.3(a)2A: Outdoor signs in tunnels, and signs in large permanently covered outdoor areas that are intended to be continuously lit, 24 hours per day and 365 days per year.  \$\frac{\}{\}\$130.3(a)2B.} \] All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  3 \]  Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	NA
If there are construction documents, indicate where on the building plans the mandatory measures (sign lighting control) note block can be located:  1 \$130.3(a)1. All indoor sign lighting is controlled with an automatic time-switch control or astronomical time-switch control.  \$130.3(a)2A. All outdoor sign lighting is controlled with a photocontrol in addition to an automatic time-switch control, or an astronomical time-switch control.  EXCEPTION to Section 130.3(a)2A: Outdoor signs in tunnels, and signs in large permanently covered outdoor areas that are intended to be continuously lit, 24 hours per day and 365 days per year.  \$130.3(a)2B. All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  3 Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	
mandatory measures (sign lighting control) note block can be located:  1 \$130.3(a)1. All indoor sign lighting is controlled with an automatic time-switch control or astronomical time-switch control.  \$130.3(a)2A. All outdoor sign lighting is controlled with a photocontrol in addition to an automatic time-switch control, or an astronomical time-switch control.  EXCEPTION to Section 130.3(a)2A: Outdoor signs in tunnels, and signs in large permanently covered outdoor areas that are intended to be continuously lit, 24 hours per day and 365 days per year.  \$130.3(a)2B. All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	
\$130.3(a)1. All indoor sign lighting is controlled with an automatic time-switch control or astronomical time-switch control.  \$130.3(a)2A. All outdoor sign lighting is controlled with a photocontrol in addition to an automatic time-switch control, or an astronomical time-switch control.  EXCEPTION to Section 130.3(a)2A: Outdoor signs in tunnels, and signs in large permanently covered outdoor areas that are intended to be continuously lit, 24 hours per day and 365 days per year.  \$130.3(a)2B. All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	
switch control.  §130.3(a)2A. All outdoor sign lighting is controlled with a photocontrol in addition to an automatic time-switch control, or an astronomical time-switch control.  EXCEPTION to Section 130.3(a)2A: Outdoor signs in tunnels, and signs in large permanently covered outdoor areas that are intended to be continuously lit, 24 hours per day and 365 days per year.  §130.3(a)2B. All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	
switch control.  §130.3(a)2A. All outdoor sign lighting is controlled with a photocontrol in addition to an automatic time- switch control, or an astronomical time-switch control.  EXCEPTION to Section 130.3(a)2A: Outdoor signs in tunnels, and signs in large permanently covered outdoor areas that are intended to be continuously lit, 24 hours per day and 365 days per year.  §130.3(a)2B. All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	NA
switch control, or an astronomical time-switch control.  EXCEPTION to Section 130.3(a)2A: Outdoor signs in tunnels, and signs in large permanently covered outdoor areas that are intended to be continuously lit, 24 hours per day and 365 days per year.  §130.3(a)2B. All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	NA
EXCEPTION to Section 130.3(a)2A: Outdoor signs in tunnels, and signs in large permanently covered outdoor areas that are intended to be continuously lit, 24 hours per day and 365 days per year.  §130.3(a)2B. All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	
EXCEPTION to Section 130.3(a)2A: Outdoor signs in tunnels, and signs in large permanently covered outdoor areas that are intended to be continuously lit, 24 hours per day and 365 days per year.  §130.3(a)2B. All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	
§130.3(a)2B. All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	NA
§130.3(a)2B. All outdoor sign lighting that is ON both day and night is controlled with a dimmer that provides the ability to automatically reduce sign lighting power by a minimum of 65 percent during nighttime hours.  Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	
Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	
Signs that are illuminated at night and for more than 1 hour during daylight hours shall be considered ON both day and night.	NA
day and night.	
EXCEPTION to Section 130.3(a)2B: Outdoor signs in tunnels and large covered areas that are intended to be	NA
illuminated both day and night.	
§130.3(a)3. Demand Responsive Electronic Message Center Control. An Electronic Message Center (EMC)	
having a new connected lighting power load greater than 15 kW has a control installed that is capable of	NA
4 reducing the lighting power by a minimum of 30 percent when receiving a demand response signal.	
	NA
ordinance, or regulation to be reduced by 30 percent.	
Field Inspector Notes:	

### STATE OF CALIFORNIA SIGN LIGHTING

CEC-NRCC-LTS-01-E(Revised 08/15)

	1	
CALIFORNIA ENERGY COMMISSION	_	٩

	ONEII ONIVI ENERGY COMMISSION
CERTIFICATE OF COMPLIANCE	NRCC-LTS-01-E
Sign Lighting	(Page 3 of 5)
Project Name:	Date Prepared:

### 2. Maximum Allowed Lighting Power Method of Compliance

Certificate of Compliance and Field Inspection Energy Checklist

Complete this part if there are signs using the maximum allowed lighting power method of compliance. (Complete part 3 of this Certificate of Compliance if there are signs using the Specific lighting sources method of compliance)

Symbol or					_			_	
or Description of the Sign Verified Label (see instructions below) Allotted Watts Watts Y/N								Field Inspector Check that sign complies	
	Sign Area (ft²)  Internally (I) or Externally (E) Illuminated Allowed LPD (I = 12 W/ft²) (E = 2.3 W/ft²) (B × F) Allowed Watts (D × F)  Total installed watts for sign								
									•
A									
С	A description of the sign, or location of sign on the building; and the location of sign on construction documents.  OPTIONAL - Check this box only if this sign has a permanent, pre-printed, factory-installed, ENERGY VERIFIED label, confirming that the sign complies with the Section 140.8 of the California 2013 Title 24, Part 6 Standards, using the Maximum Allowed Lighting Power method of compliance. The only labels that will be recognized for this purpose are ENERGY VERIFIED Certification Marks authorized by Underwriters Laboratories (UL) or other Product Certification Body accredited to ISO/IEC Guide 65 by the American National Standards Institute in accordance with ISO/IEC 17011. Surveillance by the Accredited Certification Body shall be an ongoing annual inspection program carried out by a Type A Inspection body in accordance with ISO/IEC 17020. For signs with such an ENERGY VERIFIED label, columns 'D' through 'I' are not required to be filled out. Note: Using an ENERGY VERIFIED label is an optional method to validate compliance. An ENERGY VERIFIED label is not needed for compliance.								
D	The sign area in square fe								
E	List "I" if the sign is intern			_					
F	Allowed watts per square								•
G	Multiply the square foota							F.	
Н	Show the total installed w								
I	Enter Y if the number in c		equal to	the numbe	r in column G	. Otherwis	se, the sign doe	es not comply.	
J	This page doubles as a fie	d inspection checklist.							
eld Inspe	ctor Notes:								

## STATE OF CALIFORNIA SIGN LIGHTING CEC-

NRCC-LTS-01-E(Revised 08/15)

CALIFORNIA ENERGY COMMISSION	

CERTIFICATE OF COMPLIANCE	NRCC-LTS-01-E
Sign Lighting	(Page 4 of 5)
Project Name:	Date Prepared:

3.	Specific	Lighting	Source	Method	of	Compliance
----	----------	----------	--------	--------	----	------------

Certificate of Compliance and Field Inspection Energy Checklist

Complete this part if there are signs using the Specific lighting source method of compliance. (Complete part 2 of this Certificate of Compliance if there are signs using the maximum allowed lighting power method of compliance)

	of Compliance if there are signs using the maximum allowed lighting power method of compliance)							
	Α	В	С	D	Е			
	mbo or Code	Description label Shall include only lighting Complies						
Α		bol or code used on the plans (when plans are required)						
B C		arrative description of the sign, or location of sign on the IONAL - Check this box only if this sign has a permanent,						
	othe 170: in ac ENE	labels that will be recognized for this purpose are ENER Product Certification Body accredited to ISO/IEC Guide 11. Surveillance by the Accredited Certification Body sha coordance with ISO/IEC 17020. For signs with such an EN RGY VERIFIED label is an optional method to validate cor	ational Standards Institute in accorda I inspection program carried out by a olumn 'D' is not required to be filled o 'ERIFIED label is not needed for compl	ordance with ISO/IEC y a Type A Inspection body ed out. Note: Using an				
		e following lighting technologies:						
List all applicable numbers (1 through 9) that apply in column D above for each row.  1 High pressure sodium lamps								
Metal halide lamps that are pulse start or ceramic served by a ballast that has a minimum efficiency of 8 greater. Ballast efficiency is the measured output wattage to the lamp divided by the measured operating when tested according to ANSI C82.6-2005.								
	3	Metal halide lamps that are pulse start that are 320 watts or smaller, are not 250 watt or 175 watt lamps, and are served by						
D	4	Neon or cold cathode lamps with transformer or power supply efficiency greater than or equal to a minimum efficiency of 75 percent						
	5	Neon or cold cathode lamps with transformer or power supply efficiency greater than or equal to a minimum efficiency of 68 percent						
	6	Fluorescent lighting systems meeting one of the follows 80; or B. Use only electronic ballasts with a fundamenta			endering index (CRI) of			
	7	Light emitting diodes (LEDs) with a power supply having						
	Single voltage external power supplies that are designed to convert 120 volt AC input into lower voltage DC or AC output, and have a nameplate output power less than or equal to 250 watts, shall comply with the applicable requirements of the Appliance Efficiency Regulations (Title 20).							

Field Inspector Notes:

E This page doubles as a field inspection checklist.

Compact fluorescent lamps that do not contain a medium screw base sockets (E24/E26).

## STATE OF CALIFORNIA SIGN LIGHTING CEC-

NRCC-LTS-01-E(Revised 08/15)

	7	֡
CALIFORNIA ENERGY COMMISSION	-	

1.1.1.00 2.10 0.1 2(1.10.1000 00, 10)	CALIFORNIA ENERGY COMMISSION
CERTIFICATE OF COMPLIANCE	NRCC-LTS-01-E
Sign Lighting	(Page 5 of 5)
Project Name:	Date Prepared:

DOCUMENTATION AUTHOR'S DECLARATION STATEMENT		
1. I certify that this Certificate of Compliance documentation is accurate and complete.		
Documentation Author Name:	Documentation Author Signature:	
Company:	Signature Date:	
Address:	CEA Certification Identification (if applicable):	
City/State/Zip:	Phone:	

#### **RESPONSIBLE PERSON'S DECLARATION STATEMENT**

I certify the following under penalty of perjury, under the laws of the State of California:

- 1. The information provided on this Certificate of Compliance is true and correct.
- 2. I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer).
- The energy features and performance specifications, materials, components, and manufactured devices for the building design or system
  design identified on this Certificate of Compliance conform to the requirements of Title 24, Part 1 and Part 6 of the California Code of
  Regulations.
- 4. The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application.
- 5. I will ensure that a completed signed copy of this Certificate of Compliance shall be made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable inspections. I understand that a completed signed copy of this Certificate of Compliance is required to be included with the documentation the builder provides to the building owner at occupancy.

certificate of compliance is required to be included with the documentation the ballaci provides to the ballating owner at occupancy.		
Responsible Designer Name:	Responsible Designer Signature:	
Company:	Date Signed:	
Address:	License:	
City/State/Zip:	Phone:	